

# Lavalier Microphones

## MU-53L / MU-53LS

Uni-directional Lavalier Microphone

Miniature 10mm $\phi$ . High gain before feedback.  
Warm, clear sound.



## MU-55L / MU-55LS

Omni-directional Lavalier Microphone

Sub-miniature 4.5mm $\phi$ . Low visibility.  
Extended frequency response.



- Featuring a high dynamic range and able to withstand a maximum SPL of 142 dB without distortion.
- Available in black and beige colors.
- Supplied as standard with MIPRO's 4-pin mini XLR plug.
- Features a smooth, warm, natural sound.
- Sub-miniature MU-55L has waterproof characteristic

## Specifications

Models	MU-53L / MU-53LS	MU-55L / MU-55LS
Capsule Module	10mm $\phi$ uni-directional miniature condenser microphone	4.5mm $\phi$ subminiature omni-directional condenser microphone
Frequency Response	50Hz~18KHz	40Hz~20KHz
Sensitivity	-46dBV $\pm$ 3dBV/Pa(0dB=1V/Pa)	-49dBV $\pm$ 3dBV/Pa(0dB=1V/Pa)
Maximum SPL	142dB (Typical, 1%THD)	135dB (Typical, 1%THD)
Plug	MIPRO's mini XLR 4 pin plug or TA4F	MIPRO's mini XLR 4 pin plug or TA4F
Cable Length	150 cm / 59.1"	150 cm / 59.1"
Color	Black or Beige color	Black or Beige color
Weights	Approx. 19g / 0.7oz	Approx. 14g / 0.5oz