



Technical data	
<b>Model</b>	<b>SA 70</b>
<b>Output power</b>	
rms / 8 ohms	2 x 380 W
rms / 4 ohms	2 x 610 W
bridge / 8 ohms	1.220 W
<b>Frequency response</b>	20 Hz - 20 kHz
<b>THD (20 Hz - 20 kHz)</b>	<0,03 %
<b>Talkover</b>	60 dB
<b>Slew rate</b>	45
<b>Damping factor</b>	250
<b>Voltage gain</b>	30 dB
<b>Input impedance (sym.)</b>	20 kOhm
<b>Input sensitivity</b>	0,775/1/1,44 V
<b>SNR</b>	>103 dB
<b>Power input (8 ohms)</b>	1.200 W
<b>Protection circuits</b>	
<b>Overload</b>	yes
<b>D/C</b>	yes
<b>Short circuit</b>	yes
<b>Overheat</b>	yes
<b>HF</b>	yes
<b>Clip Limiter</b>	yes
<b>Soft start</b>	yes
<b>Dimensions (mm)</b>	19"/2HE
	483 x 89 x452
<b>Weight</b>	21 kg
<b>Cooling</b>	2 fans, 2-level
<b>Inputs</b>	XLR-f/ XLR-m,parallel
<b>Outputs</b>	Speakon compliant