



XS4.4 is a compact 2-way speaker model with a priority on intelligibility, a very good efficiency and attractive design.

The internal crossover was designed by a German company specialised on speaker design, which results not only in excellent sonic performance, but also in well engineered protection circuits.

Two parallel NL-4 Speakon inputs offer easy daisy-chaining of the speaker signal. With a switch on the connection plate the input mode can be toggled between low Z or high Z with 16 ohms or 40/20/10 watts respectively.

The XS4.4 offers a great variety of mounting options: Yoke mount for both horizontal and vertical installation is available as well as a discrete wall support, which allows the installer to tilt and swivel the cabinets for optimum alignment. Above that the cabinet is Omnimount® ready for series 20.5 brackets.

Due to the conical dispersion of the HF dome, this model can be used in vertical and horizontal orientation without suffering from phase interference (e.g. under-balcony applications).

XS4.4 is available in black (similar to RAL9005), white (similar to RAL9010) or unpainted.



Tec Specs

Model	XS4.4
Power (watts / rms)	80
Rec. amplifier power	80 - 250
Driver	
LF-Driver	4"
HF-Driver	1" Dome
Input impedance	100 V / 16 ohms
100V tappings	10 / 20 / 40
Freq. response(+/-3 dB)	80 Hz - 18 kHz
SPL (1 W / 1 m)	93 dB
Dispersion (h x v)	90° x 60°
Connectors	2 x NL4 Speakon
Cabinet material	Multiplex plywood
Cabinet design	Trapezoidal
Colours available	black, white
Accessories	WB-S V-Yoke42 H-Yoke42
Special Features	Omnimount ready (20.5)
Dims (H x W x D, cm)	42.5 x 17 x 19.5
Weight (kg)	4.5