



Fuzion plc
9 Lyon Road, Walton on Thames
Surrey. UK. KT12 3PU









Phone: +44 (0)1932 882222 Fax: +44 (0)1932 882244
Email: sales@fuzion.co.uk

Web
www.fuzion.co.uk




Dated: January 2010




Professional Price List E. & O.E.










Model	Description	List Ex Vat
Amplifiers		
	TM.T&MSA20 Two channel amplifier; 2 x 150 watts @ 8 ohms, 2 x 200 watts @ 4 ohms, 1 x 400 watts @ 8 ohms in bridge mode. <ul style="list-style-type: none"> ■ Switchable input sensitivity ■ Short-circuit protection ■ Overload protection ■ DC protection ■ High temperature protection ■ 19"/1U 	£280.00
	TM.T&MSA40 Two channel amplifier; 2 x 275 watts @ 8 ohms, 2 x 400 watts @ 4 ohms, 1 x 800 watts @ 8 ohms in bridge mode. <ul style="list-style-type: none"> ■ Switchable input sensitivity ■ Short-circuit protection ■ Overload protection ■ DC protection ■ High temperature protection ■ 19"/2U 	£355.00
	TM.T&MSA70 Two channel amplifier; 2 x 380 watts @ 8 ohms, 2 x 610 watts @ 4 ohms, 1 x 1220 watts @ 8 ohms in bridge mode. <ul style="list-style-type: none"> ■ Switchable input sensitivity ■ Short-circuit protection ■ Overload protection ■ DC protection ■ Limiter ■ High temperature protection ■ 19"/2U 	£600.00
	TM.T&MSA100 Two channel amplifier; 2 x 700 watts @ 8 ohms, 2 x 1100 watts @ 4 ohms, 1 x 2200 watts/bridge @ 8 ohms. <ul style="list-style-type: none"> ■ Switchable input sensitivity ■ Short-circuit protection ■ Overload protection ■ DC protection ■ Limiter ■ High temperature protection ■ 19"/2U 	£750.00
	TM.T&MSA4200 Four channel amplifier; 4 x 130 watts @ 8 ohms, 4 x 200 watts @ 4 ohms. <ul style="list-style-type: none"> ■ Frequency response 20 Hz - 20 kHz ■ Input link-switch ■ Overload & short-circuit protection ■ DC protection ■ Limiter ■ High temperature protection ■ 19"/3U 	£520.00
	TM.T&MSA8200 Eight channel amplifier; 8 x 130 watts @ 8 ohms, 8 x 200 watts @ 4 ohms. <ul style="list-style-type: none"> ■ Frequency response 20 Hz - 20 kHz ■ Input link-switch ■ Overload & short-circuit protection ■ DC protection ■ Limiter ■ High temperature protection ■ 19"/3U 	£675.00







		Transformers	
	TM.XBOX-2	1U black steel installation rack loaded with 2 high quality 160W toroidal transformers, for use with SA4200 and SA8200. Individual Euroblock connectors for 70V and 100V output. Also compatible with any amplifier rated up to 160W.	£190.00
	TM.XBOX-4	1U black steel installation rack loaded with 4 high quality 160W toroidal transformers, for use with SA4200 and SA8200. Individual Euroblock connectors for 70V and 100V output. Also compatible with any amplifier rated up to 160W.	£300.00
		Loudspeakers - Moulded Passive	
	TM.T&M6.5P II	<p>Passive 2-way full range system in a trapezoidal rectangular polyethylene enclosure. It includes a 6.5" woofer and a 1" soft dome tweeter. 5 position switch for selecting line voltage taps or low impedance operation. Input via 2 x 4 pole speakons or banana terminals.</p> <p style="text-align: center;">Specifications:</p> <ul style="list-style-type: none"> ■ Sensitivity 91dB SPL @ 1W/1m ■ Useable frequency range 80Hz - 20KHz (+/- 3dB) ■ Max Input 50W RMS ■ Max output 109dB SPL ■ Dimensions: 360 x 200 x 232 (mm HDW) ■ Weight: 4.5kg 	£85.00
	TM.T&M6.5P/WH II	t&m6.5p II in white.	£85.00
	TM.T&M8P II	<p>Passive 2-way full range system in a trapezoidal rectangular polyethylene enclosure. It includes a 6.5" woofer and a 1" soft dome tweeter. 5 position switch for selecting line voltage taps or low impedance operation. Input via 2 x 4 pole Speakons or banana terminals.</p> <p style="text-align: center;">Specifications:</p> <ul style="list-style-type: none"> ■ Sensitivity 93dB SPL @ 1W/1m ■ Useable frequency range 60Hz - 20KHz (+/- 3dB) ■ Max Input 100W RMS ■ Max output 113dB SPL ■ Dimensions: 410 x 230 x 280 (mm HDW) ■ Weight 6Kg. 	£100.00
	TM.T&M8P/WH II	t&m8p II in white.	£100.00
		Loudspeakers - Moulded Active	
	TM.T&M6.5PA	Active 2-way full range system in a trapezoidal polyethylene enclosure. Includes a 6.5" woofer and a 1" soft dome tweeter powered by integral 50W amplifier with input gain, volume and EQ controls. The unit has an integral handle and a wall mount bracket is included. Input can be switched between mic/line with balanced input via 3 pin female XLR. Separate 3 pin male XLR aux output. All other specifications as per 6.5P II except weight increases to 7kg.	£145.00
	TM.T&M6.5PA/WH	t&m6.5pa in white.	£145.00
	TM.T&M8PA	Active 2-way full range system in a trapezoidal polyethylene enclosure. Includes an 8" woofer and a 1" soft dome tweeter powered by integral 100W amplifier with input gain, volume and EQ controls. The unit has an integral handle and a wall mount bracket is included. Input can be switched between mic/line with balanced input via 3 pin female XLR. Separate 3 pin male XLR aux output. All other specifications as per 8P II except weight increases to 10kg.	£175.00
	TM.T&M8PA/WH	t&m8pa in white.	£175.00

Accessories - Moulded Speakers			
	TM.LS-ALU	Speaker stand, black aluminium - 35mm mounting & 50 kg load. Maximum height 1.8m.	£30.00
	TM.ST-OPT	Standmount adapter. Allows the T&M8P to be mounted on a standard 35mm speaker stand.	£7.00
NEW Loudspeakers- XS Series			
	TM.XS4-B TM.XS4-W	Compact 2-way speaker offering excellent music reproduction, efficiency and contemporary design. The cabinet features an unobtrusive ball joint support which allows the installer to tilt and swivel the cabinets for optimum alignment and screw terminal inputs for quick and easy wiring. Available in black, white or unpainted, please specify when ordering. Specifications: Power: 40W RMS Recommended amplifier power: 40 - 100W LF Driver: 4" HF Driver: 1" dome Input impedance: 16 Ohms Frequency response (+/-3 dB): 80Hz - 18kHz SPL (1w/1m): 93 dB Dispersion (hxv): 90° x 90° Connectors: Screw terminals Dimensions (HxWxD): 28 x 17 x 15.5cm Weight: 3.2kg	£185.00
	TM.XS6-B TM.XS6-W	2-way speaker offering excellent music reproduction and high efficiency in a well-designed trapezoidal plywood enclosure. Two parallel NL-4 Speakon inputs allow easy daisy-chaining of the speaker signal. Due to the conical dispersion of the HF dome, this speaker can be used in vertical and horizontal orientation without suffering from phase interference. The XS6 offers a great variety of mounting options and is also Omnimount® ready for series 20.5 brackets. Available in black, white or unpainted, please specify when ordering. Specifications: Power: 100W RMS Recommended amplifier power: 100 - 250W LF Driver: 6" HF Driver: 1" dome Input impedance: 16 Ohms Frequency response (+/-3 dB): 75Hz - 18kHz SPL (1w/1m): 93 dB Dispersion (hxv): 90° x 90° Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 38.5 x 21.7 x 22cm Weight: 7.8kg	£215.00

	<p>TM.XS8-B</p> <p>TM.XS8-W</p>	<p>2-way speaker offering excellent music reproduction and high efficiency in a well-designed trapezoidal plywood enclosure. Two parallel NL-4 Speakon inputs allow easy daisy-chaining of the speaker signal. With a switch on the connection plate the input impedance can be toggled between 8, 16 and 32 Ohms. This enables the user to run a substantial number of speakers on one single amplifier channel (dependant on minimum load and power of the amplifier). The rotatable horn ensures the speaker can be used in vertical and horizontal orientation without suffering from phase interference. The XS8 offers a great variety of mounting options and is also Omnimount® ready for series 30.0 brackets. Available in black, white or unpainted, please specify when ordering.</p> <p>Specifications: Power: 150W RMS Recommended amplifier power: 150 - 300W LF Driver: 8" HF Driver: 1" with rotatable horn Input impedance: 8/16/32 Ohms Frequency response (+/-3 dB): 70Hz - 19kHz SPL (1w/1m): 95 dB Dispersion (hvx): 100° x 50° Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 50 x 28 x 27cm Weight: 12.5kg</p>	<p>£330.00</p>
	<p>TM.XS10-B</p> <p>TM.XS10-W</p>	<p>2-way speaker offering excellent music reproduction and high efficiency in a well-designed trapezoidal plywood enclosure. Two parallel NL-4 Speakon inputs allow easy daisy-chaining of the speaker signal. The rotatable horn ensures the speaker can be used in vertical and horizontal orientation without suffering from phase interference. The XS10 offers a great variety of mounting options and is also Omnimount® ready for series 30.0 brackets. Available in black, white or unpainted, please specify when ordering.</p> <p>Specifications: Power: 250W RMS Recommended amplifier power: 250 - 400W LF Driver: 10" HF Driver: 1" with rotatable horn Input impedance: 8 Ohms Frequency response (+/-3 dB): 65Hz - 19.5kHz SPL (1w/1m): 96 dB Dispersion (hvx): 100° x 50° Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 52 x 30 x 31cm Weight: 14kg</p>	<p>£360.00</p>
	<p>TM.XS12-B</p> <p>TM.XS12-W</p>	<p>2-way speaker offering excellent music reproduction and high efficiency in a well-designed trapezoidal plywood enclosure. Two parallel NL-4 Speakon inputs allow easy daisy-chaining of the speaker signal. The rotatable horn ensures the speaker can be used in vertical and horizontal orientation without suffering from phase interference. The XS12 offers a great variety of mounting options and is also Omnimount® ready for series 120.0 brackets. Available in black, white or unpainted, please specify when ordering.</p> <p>Specifications: Power: 350W RMS Recommended amplifier power: 350 - 500W LF Driver: 12" HF Driver: 1.3" with rotatable horn Input impedance: 8 Ohms Frequency response (+/-3 dB): 60Hz - 19.5kHz SPL (1w/1m): 98 dB Dispersion (hvx): 90° x 75° Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 66 x 41 x 42cm Weight: 29kg</p>	<p>£495.00</p>

	<p>TM.XS15-B TM.XS15-W</p>	<p>2-way speaker offering excellent music reproduction and high efficiency in a well-designed trapezoidal plywood enclosure. Two parallel NL-4 Speakon inputs allow easy daisy-chaining of the speaker signal. The rotatable horn ensures the speaker can be used in vertical and horizontal orientation without suffering from phase interference. The XS15 offers a great variety of mounting options and is also Omnimount® ready for series 120.0 brackets. Available in black, white or unpainted, please specify when ordering.</p> <p>Specifications: Power: 350W RMS Recommended amplifier power: 350 - 500W LF Driver: 15" HF Driver: 1.3" with rotatable horn Input impedance: 8 Ohms Frequency response (+/-3 dB): 60Hz - 19.5kHz SPL (1w/1m): 98 dB Dispersion (hvx): 90° x 75° Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 73 x 48 x 49cm Weight: 37kg</p>	<p>£540.00</p>
	<p>TM.XS2-10S-B TM.XS2-10S-W</p>	<p>Compact direct load subwoofer with two 10" LF drivers. At only 30cm high it is the perfect choice for installations offering little room, fitting very neatly under counters or small stages. Using the optional yoke bracket this subwoofer can also be installed under ceilings. The cabinet has an internal low-pass filter so that it can be fed with a full range signal and a loop-thru Speakon Out connector for connection to allow operation with full range speakers such as the XS6 or XS8. Available in black or white, please specify when ordering.</p> <p>Specifications: Power: 240W RMS Recommended amplifier power: 250 - 350W LF Driver: 2 x 10" Input impedance: 4 Ohms Frequency response (+/-3 dB): 60Hz - 250Hz SPL (1w/1m): 98 dB Dispersion (hvx): Omni Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 30 x 67 x 39cm Weight: 21kg</p>	<p>£250.00</p>
	<p>TM.XS15S-B TM.XS15S-W</p>	<p>Direct load subwoofer with one 15" LF long stroke driver. The cabinet has an internal low-pass filter so that it can be fed with a full range signal and a loop-thru Speakon Out connector for connection to allow operation with full range speakers such as the XS10 or XS12. Paired with the XS8 or XS10 it provides a depth and clarity perfect for small-medium sized venues. Available in black or white, please specify when ordering.</p> <p>Specifications: Power: 400W RMS Recommended amplifier power: 350 - 500W LF Driver: 15" Input impedance: 4 Ohms Frequency response (+/-3 dB): 55Hz - 250Hz SPL (1w/1m): 100 dB Dispersion (hvx): Omni Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 58 x 51 x 55cm Weight: 35kg</p>	<p>£500.00</p>

	<p>TM.XS18S-B TM.XS18S-W</p>	<p>Direct load subwoofer with one 18" LF long stroke driver. The cabinet has an internal low-pass filter so that it can be fed with a full range signal and a loop-thru Speakon Out connector for connection to allow operation with full range speakers such as the XS12 or XS15. Paired with these full range cabinets you'll find a level of audio quality rarely seen at this price. Available in black or white, please specify when ordering.</p> <p>Specifications: Power: 600W RMS Recommended amplifier power: 450 - 800W LF Driver: 18" Input impedance: 4 Ohms Frequency response (+/-3 dB): 55Hz - 250Hz SPL (1w/1m): 101 dB Dispersion (hvx): Omni Connectors: 2 x NL4 Speakon Dimensions (HxWxD): 67.5 x 56 x 62 cm Weight: 45kg</p>	<p>£750.00</p>
Accessories - Loudspeakers			
	<p>TM.WB35</p>	<p>Wall support compatible with 35mm speaker stand adaptor; allows to tilt and swivel the cabinets for optimum alignment. Available in black or white, please specify when ordering.</p>	<p>£85.00</p>
	<p>TM.WB-S</p>	<p>Steel wall support for XS4.2, XS4.4, XS6, XS8 and XS10; allows the user to tilt and swivel the cabinets for optimum alignment. Available in black or white, please specify when ordering.</p>	<p>£46.00</p>
	<p>TM.WB-4</p>	<p>Wallmount bracket for use with XS4. Formed of glass fibre nylon, the bracket allows tilt angles of up to 50 degrees for optimum alignment. Available in black or white, please specify when ordering.</p>	<p>£49.00</p>
<p><i>no image available</i></p>	<p>TM.WB-L</p>	<p>Steel wall support for XS12 and XS15; allows the user to tilt and swivel the cabinets for optimum alignment. Available in black or white, please specify when ordering.</p>	<p>£52.00</p>
	<p>TM.V-YOKE6</p>	<p>Steel vertical yoke mount for XS6. Available in black or white, please specify when ordering.</p>	<p>£48.00</p>
	<p>TM.H-YOKE6</p>	<p>Steel horizontal yoke mount for XS6. Available in black or white, please specify when ordering.</p>	<p>£49.00</p>
	<p>TM.V-YOKE8</p>	<p>Steel vertical yoke mount for XS8. Available in black or white, please specify when ordering.</p>	<p>£52.00</p>
	<p>TM.H-YOKE8</p>	<p>Steel horizontal yoke mount for XS8. Available in black or white, please specify when ordering.</p>	<p>£55.00</p>
	<p>TM.V-YOKE10</p>	<p>Steel vertical yoke mount for XS10. Available in black or white, please specify when ordering.</p>	<p>£54.00</p>

	TM.H-YOKE10	Steel horizontal yoke mount for XS10. Available in black or white, please specify when ordering.	£57.00
	TM.V-YOKE12	Steel vertical yoke mount for XS12. Available in black or white, please specify when ordering.	£63.00
	TM.H-YOKE12	Steel horizontal yoke mount for XS12. Available in black or white, please specify when ordering.	£66.00
	TM.V-YOKE15	Steel vertical yoke mount for XS15. Available in black or white, please specify when ordering.	£68.00
	TM.H-YOKE15	Steel horizontal yoke mount for XS15. Available in black or white, please specify when ordering.	£72.00
	TM.YOKE210S	Steel yoke mount for XS2.10S. Available in black or white, please specify when ordering.	£59.00